

ELECTRICAL WATER HEATER



Electrical Hot Water Heater

These electrical water heaters, that are produced according to European Standard (EN 12897), are given preference in areas which don't have the source of heating liquid to respond hot water demand by using electric energy.

The security of electric control panel in this product is upgraded to maximum level. In the electric control panel, mainly there are fuse, contact, thermostat of security and operation, on/off switch and the relay of contact fault stream.


Moreover, different capacities and electric power of this product can be made also by using security valve that is sensitive to temperature and pressure as optional.

Technical features

- Capacity between 100 - 3000 lt.
- Hygienic because areas, that come into contact with water, are plated with two coats of enamel...
- 50 mm. Polyurethane insulated at all capacities.
- Electrostatics powder painted cover on galvanized plate at all capacities.
- Cathodic protection.
- High efficiency.
- Rustless resistances.
- Esthetic appearance.
- 10 bar operating pressure.



ELECTRICAL HOT WATER HEATER



CONNECTION SCHEME

1. T&P Valve
2. Open - Closed valve
3. Manometers
4. Check valve
5. Circulation Pump
6. Strainers

MODELS

ATA 103	100 LT	ATA 603	600 LT
ATA 163	160 LT	ATA 803	800 LT
ATA 203	200 LT	ATA 1003	1000 LT
ATA 303	300 LT	ATA 1503	1500 LT
ATA 503	500 LT	ATA 2003	2000 LT
		ATA 3003	3000 LT

CAPACITY SCHEME

MODEL	CAPACITY (LT)	ELECTRIC POWER (KW)	HOT WATER CAPACITY (LTH) 18/45°C
ATA 103	100	1x4	98
ATA 163	160	2x3	147
ATA 203	200	2x4	196
ATA 303	300	2x7	245
ATA 503	500	2x10	491
ATA 603	600	2x12	583
ATA 803	800	2x16	740
ATA 1003	1000	3x10	1108
ATA 1503	1500	4x10	1473
ATA 2003	2000	6x10	1840
ATA 3003	3000	8x10	2548

Our products are suitable for 223 V or 380 V, 50Hz. We may produce special water heaters for 110V and 60 Hz. Please contact us for bigger or different capacities.

MODEL	ATA 103	ATA 163	ATA 203	ATA 303	ATA 503	ATA 603	ATA 803	ATA 1003	ATA 1503	ATA 2003	ATA 3003
CAPACITY (LT)	100	160	200	300	500	600	800	1000	1500	2000	3000
DIAMETER(mm)	456	586	686	756	756	756	910	1010	1120	1260	1440
HEIGHT (mm)	1100	1100	1300	1320	1770	2020	2150	2180	2470	2500	2700
COLD WATER INLET	3/4"	3/4"	3/4"	1"	1"	1"	1 1/4"	1 1/4"	1 1/2"	1 1/2"	2"
HOT WATER OUTLET	3/4"	3/4"	3/4"	1"	1"	1"	1 1/4"	1 1/4"	1 1/2"	1 1/2"	2"
CIRCULATION PUMP	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	1"	1"	1 1/4"	1 1/4"	1 1/2"
NET WEIGHT(kg)	66	74	89	106	177	194	250	310	417	560	890

ATABOYLER

"The New Form Of Energy"

ATADEMİR TUR. İNŞ. MAK. SAN. TİC. LTD. ŞTİ.

Modern Katedraşlar Sitesi 4. Cd. 16.Sk. No:3-5-7 Saray-Kazan - ANKARA / TÜRKİYE Phone: 0 (312) 815 13 97 Fax: 0 (312) 815 13 98
www.ataboyler.com • info@ataboyler.com